

*Secret*  
**SECRET****PROHIBIT**

OUT53514

P 290342Z  
 FM NPIC WASHDC  
 TO RUCSBR/SAC OFFUTT AFB OMAHA NEB  
 RUCVAB/4080 STRAT WG OL 19 BARKSDALE AFB LA  
 RUCVAB/2D RTS BARKSDALE AFB LA  
 RUEAHQ/DIA WASHDC  
 RUECYG/NAVRECONTECHSUPPCEN SUITLAND MD  
 RUWBKN/15TH AF MARCH AFB RIVERSIDE CALIF  
 RUWGAA/2AF BARKSDALE AFB LA  
 DA GRNC  
 BT  
 S E C R E T CITE NPIC 2353

1964 MAY 29 04 11Z

~~HPS~~ \_\_\_\_\_  
~~CJS~~ \_\_\_\_\_  
~~CEC~~ \_\_\_\_\_  
~~PNS~~ \_\_\_\_\_  
~~ACL~~ \_\_\_\_\_

15TH AF (FOR DI), SAC (FOR DIM/GOLDEN TREE/DOCR, DM 4) 2D AF (FOR DI) Grace (File)

1. CAMERA B 15 WAS USED IN MISSION 3903 FLOWN ON 26 MAY 1964;  
 PROCESSING WAS ACCOMPLISHED BY NAV RECON TECH SUPPCEN.

2. ORIGINAL NEGATIVE:

A. THE EXPOSURE WAS ADEQUATE AND THE RESOLUTION IS GOOD WHERE  
 NOT DEGRADED BY ATMOSPHERIC CONDITIONS.

B. 9R SIDE: MINOR EDGE STATIC IS FOUND INTERMITTENTLY THROUGH-  
 OUT THE MISSION ALONG THE INBOARD EDGE. MINUS DENSITY DOTS, SPACED  
 1.55" APART, APPEAR IN ROWS PARALLEL TO AND 3.65" FROM THE OUTBOARD  
 AND 1.10" FROM THE INBOARD EDGE OF THE FILM. SHORT, FINE, PLUS  
 DENSITY LINES ARE NOTED PARALLEL TO THE MINOR AXIS WHEN THE DENSITY  
 OF THE FILM IS AT A FAVORABLE LEVEL. A MINOR PLUS DENSITY LINE IS  
 PRESENT INTERMITTENTLY PARALLEL TO AND 3.25" FROM THE INBOARD EDGE.  
 SEVERAL BLISTERS ARE LOCATED ON FRAME 1033. A HEAT SPLICE,  
 REPLACING A MANUFACTURING SPLICE, IS LOCATED ON FRAME 1281.

C. 9L SIDE: STATIC DISCHARGES ARE PRESENT ON THE INBOARD

9507



-PAGE 2-

AND OUTBOARD EDGES OF THE FILM. THE INBOARD SIDES OF THE FORMATS CONTAIN ROLLER-INDUCED STATIC DISCHARGES. PINHOLES ARE PRESENT INTERMITTENTLY THROUGHOUT THE MATERIAL. CREASES DEGRADE FRAMES 528, 529, 1688 AND 1689. A HEAT SPLICE IS POSITIONED BETWEEN FRAMES 531/532 AND ANOTHER IS PRESENT WITHIN THE FORMAT OF FRAME 1332. FRAME 604 CONTAINS A MANUFACTURER'S SPLICE.

D. BOTH SIDES: THE FIDUCIALS ADJACENT TO THE OUTBOARD EDGE OF THE DATA CHAMBER ENDS OF THE FORMATS ARE PARTIALLY CUT OFF. THIS CONDITION IS MORE SEVERE ON THE 9R SIDE. BOTH SIDES CONTAIN TITLED FRAMES 0000-2639 BUT FRAME 2639 IN THE 9L SIDE CONSISTS OF ONLY ONE-THIRD OF A FORMAT.

3. POSITIVE:

- A. THE PI SUITABILITY IS GOOD.
- B. PRINTING AND PROCESSING ARE GOOD.
- C. CLOUDS OBSCURE 35 PERCENT OF THE PHOTOGRAPHY.

S E C R E T

-END OF MESSAGE-

(ALSO PASSED TO CIA WATCH (CGS))